

## Tegile T3600

### All-Flash for Primary Workloads

Ideal for those looking to accelerate business applications that require high I/O and low latency.

Tegile IntelliFlash data reduction techniques can improve effective capacity by up to 10x.



Model	T3600
<b>Platform Configuration</b>	
Type	All-Flash Array
DRAM Memory	192 GB
Flash Memory	12 TB
<b>Storage Capacity</b>	
Min / Max: Raw Capacity	12TB / 300TB
<b>Physical</b>	
Form Factor (Rack Units)	2U
Weight (Lbs)	80
Power (W)	450
<b>Network Connections</b>	
1 Gbps Ethernet Ports	12
1 Gbps IP-KVM Lights-out Mgmt. Port	2
Optional Connectivity	Dual-port 4/8 Fibre-Channel, Dual-port 10 GbE Copper/Fiber, Quad-port 1 Gbps Ethernet
<b>Expansion Shelves</b>	
ESF-10/25/50	Up to 4 shelves
ESF-145	Up to 2 shelves
<b>Software Services Included</b>	
Protocols	SAN (iSCSI, FC), NAS (NFS, CIFS, SMB)
Data Services	De-duplication, Compression, Thin Provisioning, Snapshots, Remote Replication, Application-Aware Provisioning
Management	Web browser, SSH, IP-KVM
Data Security	Inline 256-bit AES encryption for data at rest (available only on factory-installed arrays with IntelliFlash OS 3.x)
Redundancy	No single point of failure, Active-Active High Availability Architecture
<b>Warranty &amp; Support</b>	
Basic	24x7 support via email and phone, next business day hardware replacement for defective parts and software updates for first 90 days.
Optional	See <a href="#">IntelliCare Support Program</a> for more information